



SOLID
TO SUCCEED

AS

ROUGH TERRAIN SCISSOR LIFT XG1523RT

Standard configuration

Work Area

- Foldable Guardrail
- Self-Closing Gate
- Bidirectional Platform Extension
- Anti-Slipping Metal Platform
- Lanyard Attach Points

Drive

- 4-Wheel Drive
- Front-Wheel Steering
- 40 % Gradeability

Performance

- Full Proportion Travel And Lift Control
- Axle Oscillation System

Power

- Kobota Engine(EU V)
- Applicability
- Lubrication-Free Bearing

Safe

- Emergency Stop Button
- Movement Alarm
- Flashing Indicator Light
- Boom Maintenance Lock
- Automatic Drive Restriction At Height
- Tilt Protection System
- Auto Brake System
- Fault Diagnosis System
- Emergency Descent System
- Hydraulic Oil Cooling System
- Outrigger Leveling System
- Engine Condition Monitoring And Start Protection System
- Load Sensing Alarm System

Other Features

- Standard Forklift Pockets For Transport
- Tie Down And Lifting Points
- Electric Horn
- Fuel Level Display
- Pull-Out Engine Tray
- Hourmeter
- User-Friendly Control System
- Platform External Power Supply



Working height
15 meters



Lift capacity
680Kg



Diesel
power



Optional configuration

- Low-Speed Drive At Height
- Chassis Protective Fence
- Non-Marking Rubber Tire

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XG1523RT





SOLID
TO SUCCEED


Rough Terrain Scissor Lift-Engine Powered

Item	Metric
Dimension	
Max. Working Height	15 m
Max. Platform Height	13 m
Min. Platform Height	1.8 m
Max. Platform Drive Height	3 m (Standard) 13 m (Optional)
Overall Length	4860 mm
Overall Width	2286 mm
Overall Height (Platform Folded)	2950 (2290) mm
Platform Length	3980 mm
Platform Width	1830 mm
Platform Extension Length	1450 mm/1140 mm
Outrigger Span (Side To Side/ Front And Rear)	1995 mm/4280 mm
Wheelbase	2850 mm
Min. Ground Clearance	253 mm
Tire Size	835 mm×290 mm
Performance	
Rated Load	680 kg
Load On Platform Extension	230 kg
Max. Platform Occupancy (Indoor/Outdoor)	7/7
Max. Driving Speed (Stowed)	6.1 km/h
Max. Driving Speed (Raised)	0 km/h (Standard) 11 km/h (Optional)
Max. Gradeability	40%
Min. Turning Radius (Inside)	2.5 m
Min. Turning Radius (Outside)	5.6 m
Platform Raising Time	45 s
Platform Lowering Time	45 s
Max. Working Slope (Side To Side/Front And Rear)	2°/3°
Tire Ground Pressure	13.3 kg/cm ²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	2
Power Source	
Engine Model	Kubota V2403
Engine Power / Rpm	36.8 kW/2700 rpm
Max. Engine Torque	158 N · m
Hydraulic Oil Capacity	
Hydraulic Tank Capacity	115 L
Fuel Tank Capacity	115 L
Weight	
Machine Weight	7250kg

Trans



Platform Extd



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.