

XGS28K2



SOLID
TO SUCCEED


Telescopic Boom Lift-Engine Powered

Item	Metric	
Dimensions		
Overall Dimension - Stowed	Length	11690mm
	Width	2490mm
	Height	2820mm
Overall Dimension - Transported	Length	9550mm
	Width	2490mm
	Height	3100mm
Platform Dimensions	Length	2400mm
	Width	900mm
	Height	1150mm
Wheelbase		3000mm
Jib Length		1850mm
Min. Ground Clearance		320mm



Performance	
Max. Working Height	28.8m
Max. Platform Height	26.8m
Max. Outreach	22m
Max. Lift Capacity	300/460kg
Max. Platform Occupancy	2/3
Max. Chassis Allowable Angle	X-5° / Y-5°
Telescopic Boom Luffing Range	-4° ~ 73°
Fly Boom Luffing Range	-65° ~ 70°
Turntable Rotation	360°
Platform Rotation	160°
Machine Weight	17300kg
Driving Speed (Stowed)	5.5km/h
Driving Speed (Raised Or Extended)	0.6km/h
Min. Turning Radius (Inside/Outside)	4400mm/6250mm
Turntable Tailswing (Stowed)	1890mm
Max. Gradeability (Counterweight Uphill)	45% (24°)

Power Source	
Control	12 V DC proportional control
Emergency Power Supply	12V/200Ah
Engine Model	Cummins QSF2.8
Engine Power / Rpm	53kW(2200r/min)
Max. Engine Torque	270N · m(1500r/min)
Engine Emission Standard	Stage III
Hydraulic Tank Capacity (Effective Volume)	130L
Fuel Tank Capacity	180L



Tire	
Tire Size	φ1000mm×388mm
Tire Ground Pressure	9.39 kg/cm ²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	2



Stowed



Trans





SOLID
TO SUCCEED

TELESCOPIC BOOM LIFT

XGS28K2

Standard configuration

Work Area

- Tri-Entry Platform With Side Swing Gate

Power

- Cold Start Components
- Engine Intake Air Pre-Filter Assembly
- Engine Condition Monitoring And Start Protection Device

Drive

- Axle Oscillation

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Horn With Adjustable Volume
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- Axle Oscillation Pressure Detection System
- 4-Wheel Braking System

Other Features

- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Two-Speed Drive
- Telematics Front-End Interface
- Anti-Entrapment System
- Hostile Environment Package
- Thumb Rocker Steering



Working height
28.8 meters



Lift capacity
300/460Kg



Diesel
power



Optional configuration

- Foam-Filled Tires
- Tool Tray
- Platform Power
- Mechanical Anti-Entrapment Device
- Air Line
- Working Light Assembly
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Platform Half-Mesh

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com