



SOLID
TO SUCCEED

ARTICULATED BOOM LIFT XGA43K

Standard configuration

- **Work Area**
- Tri-Entry Platform With Side Swing Gate
- **Power**
- 12V DC Auxiliary Power
- Cold Start Components
- Engine Intake Air Pre-Filter Assembly
- Engine Condition Monitoring And Start Protection Device
- **Drive**
- 4-Wheel Drive
- **Safe**
- Descent And Motion Alarm
- Tilt Alarm
- Horn
- Overload Alarm
- Work Platform Tilt Protection
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- 4-Wheel Braking System
- **Other Features**
- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Two-Speed Drive
- Hostile Environment Package
- Hydraulic Oil Cooling System
- Telematics Front-End Interface
- Anti-Entrapment System
- Tool Tray



Working height
43.2 meters



Lift capacity
300/460Kg



Diesel
power



Optional configuration

- Hydraulic Generator
- Mechanical Anti-Entrapment Device
- Working Light Assembly
- Platform Half-Mesh
- Air Line
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Aircraft Protection Device
- Platform Height Limitation Anti-Collision Device
- Rubber Buffer Protection Device
- Anemometer
- Platform Power

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com


XGA43K





SOLID
TO SUCCEED

Articulated Boom Lift-Engine Powered



Item	Metric	
Dimensions		
Overall Dimension - Stowed	Length	12928mm
	Width	2490mm
	Height	3100mm
Overall Dimension - Transported	Length	11900mm
	Width	2490mm
	Height	3100mm
Platform Dimensions	Length	2400mm
	Width	900mm
	Height	1150mm
Wheelbase (Axle Retracted/Axle Extended)		4630mm/4256mm
Overall Width (Axle Retracted/Axle Extended)		2490mm/4400mm
Jib Length		2540mm
Min. Ground Clearance		390mm
Performance		
Max. Working Height		43.2m
Max. Platform Height		41.2m
Max. Outreach		21.6m
Max. Up And Over Clearance		18.9m
Max. Down Reach Depth		2.8m
Max. Lift Capacity		300kg/460kg
Max. Platform Occupancy		2/3
Max. Chassis Allowable Angle		X-5°/ Y-5°
1St Boom Luffing Range		-4°~ 68°
2Nd Boom Luffing Range		-64°~ 75°
Fly Boom Luffing Range		-65°~ 66°
Turntable Rotation		360°
Platform Rotation		160°
Machine Weight		24500kg
Driving Speed (Stowed)		4.5km/h
Driving Speed (Raised Or Extended)		0.5km/h
Min. Turning Radius-Axle Retracted (Inside/Outside)		17620mm /19590 mm (2) 8650mm /10630 mm (4)
Min. Turning Radius-Axle Extended (Inside/Outside)		5495 mm /8735 mm (2) 2595 mm /6025 mm (4)
Turntable Tailswing		3795mm
Max. Gradeability (Counterweight Uphill)		40% (22°)
Power Source		
Control		12 V DC Proportional Control
Emergency Power Supply		12V/2×220Ah
Engine Model		Cummins QSF2.8
Engine Power / Rpm		53KW(2200r/min)
Max. Engine Torque		270N · m(1500-1800r/min)
Engine Emission Standard		Stage III
Hydraulic Oil Tank Capacity (Effective Volume)		420L
Fuel Tank Capacity		210L
Tire		
Tire Size		Φ1162mm×445mm
Tire Ground Pressure		7kg/cm²
Driving Wheels		4
Braking Wheels		4
Steering Wheels		4



Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.