



SOLID
TO SUCCEED



TELESCOPIC BOOM LIFT XGS20ACK

Standard configuration

Work Area

- Tri-Entry Platform With Side Swing Gate

Power

- 12V DC Auxiliary Power
- 48V Battery System

Drive

- Axle Oscillation

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Horn With Adjustable Volume
- Overload Alarm
- Motor Overload Protection
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- 4-Wheel Braking System

Other Features

- Platform Self-Leveling
- Proportional Joystick Control
- Drive Enable
- Hostile Environment Package
- 360° Continuous Turntable Rotation
- Telematics Front-End Interface
- Anti-Entrapment System
- Boom Gravity Descent System
- Platform Power
- Tool Tray



Working height
20.5 meters



Lift capacity
300kg



Electric
power



Optional configuration

- Working Light Assembly
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Platform Half-Mesh
- Mechanical Anti-Entrapment Device
- Main Power Source - Battery (Lithium Battery: 51.2V/412Ah)

XCMG FIRE-FIGHTING SAFETY EQUIPMENT CO., LTD

No.17 Zhujiang East Road, Hi-Tech Development Zone, Xuzhou, Jiangsu, China
mewp@xcmg.com

XGS20ACK



SOLID
TO SUCCEED


Telescopic Boom Lift-Electric

Item Dimension		Metric	
		Maintenance-free lead-acid battery	Lithium battery
Overall Dimension - Stowed	Length	9800mm	9800mm
	Width	2490mm	2490mm
	Height	2640mm	2640mm
Overall Dimension - Transported	Length	7400mm	7400mm
	Width	2490mm	2490mm
	Height	3000mm	3000mm
Platform Dimensions	Length	1830mm	1830mm
	Width	760mm	760mm
	Height	1150mm	1150mm
Wheelbase		2500mm	2500mm
Jib Length		1850mm	1850mm
Min. Ground Clearance		300mm	300mm



Performance		
Max. Working Height	20.5m	20.5m
Max. Platform Height	18.5m	18.5m
Max. Outreach	13.2m	13.2m
Max. Lift Capacity	300kg	300kg
Max. Platform Occupancy	2	2
Max. Chassis Allowable Angle	X-5°/Y-5°	X-5°/Y-5°
Telescopic Boom Luffing Range	-5°~76°	-5°~76°
Fly Boom Luffing Range	-65°~70°	-65°~70°
Turntable Rotation	360°	360°
Platform Rotation	160°	160°
Machine Weight	8600kg	8350kg
Driving Speed (Stowed)	4.8km/h	4.8km/h
Driving Speed (Raised Or Extended)	0.6 km/h	0.6 km/h
Min. Turning Radius (Inside/Outside)	3100mm/5000mm	3100mm/5000mm
Turntable Tailswing (Stowed)	1630mm	1630mm
Max. Gradeability (Counterweight Uphill)	45% (24°)	45% (24°)

Power source		
Control	12 V DC proportional control	12 V DC proportional control
Main Power Unit	12kW/31V (AC)	12kW/31V (AC)
Auxiliary Power Unit	1.9kW/12V (DC)	1.9kW/12V (DC)
Traveling Motor	3.3kW/32V (AC)	3.3kW/32V (AC)
Emergency Power Supply	12V/120Ah	12V/120Ah
Main Power Source - Battery	48V/400Ah	51.52V/456Ah
Main Power Source - Charger	48V/40A	48V/60A
Hydraulic Oil Tank Capacity (Effective Volume)	103L	103L



Tire		
Tire Size	Φ834mm×270mm	Φ834mm×270mm
Tire Ground Pressure	6.92kg/cm ²	6.72kg/cm ²
Driving Wheels	4	4
Braking Wheels	4	4
Steering Wheels	2	2



Stowed



Trans



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvement requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.